



Cooler Master has revived the legendary Hyper 212 EVO with major improvements. Upgraded with an asymmetrical heat pipe design, it now provides 100% RAM clearance for guaranteed compatibility across motherboards. The cooler stature has been shortened as well, making case compatibility even better. Cooler Master's exclusive Direct Contact Technology, paired with the new SickleFlow 120 Fan delivers the ultimate balance of cooling performance and quiet operation. Additionally, the universal brackets have been improved further, making installation simple and hassle free.

HYPER 212 EVO V2





Asymmetrical Design Asymmetrical heat pipe design delivers maximum RAM compatibility and clearance space



Direct Contact Technology

Direct Contact Technology using 4 copper heat pipe maximize surface area for optimal heat dissipation



SickleFlow 120 Fan Newly redesigned curved blades with enhanced framework provides optimum airflow, static air-pressure, and noiseless operation





Universal Mounting Kits

Universal brackets including LGA 1700 & AM5 compatibility simplifies installation. New SickleFlow 120 Fan - Redesigned curved blades and frame optimizes airflow and static pressure

Asymmetrical 4 Heat Pipe Design - Asymmetrical heat pipe design delivers maximum RAM compatibility and clearance space across various motherboard platforms

Direct Contact Technology - Direct Contact Technology using 4 copper heat pipes deliver exceptional heat dissipation Precise Combination of Air Flow and Heat sink - Stacked-fin array provides low airflow resistance allowing cooler air flow through the heat sink

Quiet Operation - Performance silent fan with minimized vibrations provides noiseless operation

Snap and Play - Intuitive bracket design allows for a hassle free installation process

SPECIFICATIONS

Product Name	Hyper 212 EVO V2			
Product Number	RR-2V2E-18PK-R2			
Exterior Color	Silver			
	Intel® LGA 1700 / 1200 / 2066 / 2011-v3 / 2011 / 1156 / 1155 / 1151 / 1150			
CPU Socket	AMD® AM5 / AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1			
Dimensions	120 x 80 x 154 mm (4.7 x 3.1 x 6.1 inch)			
Heat Sink Material	4 Heat Pipes / Direct Contact/ Aluminum Fins			
	Dimensions (L x W x H)	120 x 120 x 25 mm (4.7 x 4.7 x 1 inch)		
	Quantity (pcs)	1 PC		
	Speed (RPM)	650 ~ 1800 RPM ± 5%		
	Airflow (CFM)	62 CFM (Max)		
	Noise Level (dBA)	8 ~ 27 dB(A)		
F	Pressure (mmH2O)	2.5 mmH ₂ O (Max)		
Fan	MTTF	>160,000 hours		
	Power Connector	4-Pin (PWM)		
	Rated Voltage (VDC)	12 VDC		
	Rated Current (A)	0.15 A		
	Safety Current	0.37 A		
	Power Consumption	1.8 W		
Warranty	nty 2 years			

PACKING INFORMATION

EAN code	4719512123478
UPC code	884102095795
Net weight	1.19 kg
Gross weight	1.45 kg
Package dimension (L x W X H)	15.7 x 9.9 x 22.8cm
Carton dimension (L x W x H)	53.0 x 33.5 x 26.0cm
Units/CTN	10

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	4200	42	N/A
40'	8400	84	N/A
40 HQ	9600	96	N/A