



The Hyper 212 LED Turbo ARGB showcases our upgraded SickleFlow 120 ARGB fans with a dual fan setup for Push-Pull configuration. The fans boast an upgrade fan blade and frame design to enhance cooling capabilities while maintaining silent operation. With Addressable RGB and included mini addressable RGB controller certified for compatibility with various ARGB motherboards, it adds the touch of vibrancy to your build. Complimenting the aesthetics, it is designed with the jet black aluminum top cover for a premium finish. Its 4 heat pipes using Direct Contact Technology ensures a smooth contact surface to provide exceptional cooling efficiency.

HYPER 212 LED TURBO ARGB



Direct Contact Technology

Direct Contact Technology using 4 copper heat pipes delivers exceptional heat dissipation



Mini Addressable RGB LED Controller

Included Mini ARGB controller gives you versatility for your favorite color arrays.



Premium Aluminum Black Top Cover

Black aluminum top cover offers a premium finish



Dual SickleFlow ARGB Fan

Redesigned curved blades and frame optimizes airflow and air pressure

Mini Addressable RGB LED Controller-Included Mini ARGB controller gives you versatility for your favorite color arrays.

Premium Aluminum Black Top Cover - Black aluminum top cover offers a premium finish

Dual SickleFlow 120 ARGB Fan - Redesigned curved blades and frame optimizes airflow and air pressure

Direct Contact Technology - Direct Contact Technology using 4 copper heat pipes delivers exceptional heat dissipation



SPECIFICATIONS

Product Name	Hyper 212 LED Turbo ARGB	
Product Number	RR-212TK-18PA-R1	
Exterior Color	Black & Silver	
CPU Socket	Intel® LGA 1700 / 1200 / 1151 / 1150 / 1155 / 1156 socket	
	AMD® AM5 / AM4 socket	
Dimensions (Lx W x H)	120 x 110 x 159 mm (4.7 x 4.3 x 6.3 inch)	
Heat Sink Material	4 Heat Pipes / Direct Contact / Aluminum Fins	
Fan		120mm Fan
	Dimensions (L x W x H)	120 x 120 x 25mm (4.7 x 4.7 x 1 inch)
	Profile	Addressable RGB
	Quantity (pcs)	2 PCS
	Speed	650 ~ 1800 RPM ± 5%
	Airflow (Max)	105.3 m³/h (62 CFM)
	Pressure (Max)	2.5 mmH₂O
	MTTF	>16,000 Hours
	Noise Level (Max)	27 dB(A)
	Bearing	Rifle
	Power Connector	4-Pin PWM
	Rated Voltage	12 VDC
	Rated Current	0.15 A
	Safety Current	0.37 A
	Power Consumption	1.8 W
Warranty	2 years	

PACKING INFORMATION

EAN code	4719512110157
UPC code	884102082467
Net weight	0.83 kg
Gross weight	1.07 kg
Package dimension (L x W X H)	658 x 325 x 240 mm
Carton dimension (L x W x H)	157 x 129 x 228 mm
Units/CTN	10

	Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
	20'	3200	42	N/A
	40'	6400	42	N/A
	40 HQ	7200	548	N/A

