## Nebula Plus & Professional Packs Feature List

M M	2 R	F	s	W	Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
•		~	<b>✓</b>	✓	sets	Handy tools to manage group(s) consisting with two or more Pro orgs that you own, including Monitor - Overview, Inventory, Change log and Configure - Settings, Org-to-Org VPN, and Administrators.  Besides the Org-to-Org VPN which is used to manage cross-org VPN and its service, other settings share the same name features as Organization-wide but from the group perspective.				VAR&IT	Group-wide (appears if at least one group of organizations is created)	*Only NCC Admin owns more than 2 Pro orgs could create group.
•	✓	<b>√</b>	<b>∕</b> √	✓		Every changes on your org. will be recorded so that you can check what settings have been made by whom and when.			•		Organization-wide > Organization-wide manage > Change log	
	<b>)</b>	<b>√</b>	/ /	<b>√</b>	Login IP address ranges for an organization	List the IP addresses or ranges from which an administrator is allowed to log into the NCC.	(Follow NCC setting)		•	MSP	Organization-wide > Orgranization-wide manage > Organization settings	
•	<b>√</b>	<b>√</b>	<b>✓</b>	✓		No limits on the number of admin (5 only on Base Pack).		8		MSP	Organization-wide > Administrators	
•		<b>√</b>	<b>/</b>	<b>√</b>	Cloud Authentication Users with unlimited entries	Allow unlimited authorized entries for the NCC cloud user database (50 only on Base Pack).		100		VAR&IT	Organization-wide > Organization-wide manage > Cloud authentication	
	)			✓		Support dynamic VLAN assignment on WPA2/3 enterprise authentication with Nebula cloud auth.			•		Organization-wide > Organization-wide manage > Cloud authentication (Account type: Users)	
				<b>√</b>	Cloud Authentication DPPSK Account Type	Allow to create single or batch personal preshared key and send to applicant by email for wireless secure connection.			•	VAR&IT	Organization-wide > Configure > Cloud authentication (Account type: DPPSK)	
•		<b>√</b>	<b>/</b> √	<b>√</b>	New site configuration clone	Replicate the configuration of an existing site instead of using the default settings while creating a new site.			•	VARAII	<ol> <li>Site drop-down box &gt; + Create site</li> <li>Organization-wide &gt; Organization-wide manage &gt; Organization portal &gt; Create site</li> </ol>	
•				<b>√</b>	Configuration site based settings sync	Allows to easily propagate Site-wide general settings and AP SSID related configurations from one site to other sites under an org.			•	MSP	Organization-wide > Organization-wide manage > Configuration management	

									17.20
M M2 R	F S	W	Feature Name	Feature Description	APP	Plus Pack Pro Pack	Target Use		Note
•	٧	/	Configuration switch settings clone	Clone switch device based settings from one device to others of the same model under an org.			MSP	Organization-wide > Organization- wide manage > Configuration management	
• 🗸	√ v	<b>✓</b> ✓	Configuration backup/restore	Backup and restore your settings of your sites and switch devices.		•	VAR&IT	Organization-wide > Organization- wide manage > Configuration management	
•	٧	/ /	Configuration template*	Allow many sites to be deployed and keep updated following a single base configuration template.			MSP	Organization-wide > Organization- wide manage > Configuration templates	*Currently Security Appliance & Mobile Router configuration have not yet supported.
•		✓	Connection log (former name Client Diagnostics)	New tab page of Clients that aims to provide friendly and end-to-end complete connection journey based logs to help administrators easily pinpoint client's connection issues		•	VAR&IT	Site-wide > Clients > Connection log	
•		<b>√</b>	WiFi Aid	The latest tab page of Clients that aims to provide adminstrators a comprehesive dashboard and reports of WiFi client's connection issues			VAR&IT	Site-wide > Clients > WiFi Aid Site-wide > Monitor > Access points > WiFi Aid	
• ✓	√ v	<b>✓</b> ✓	Site-wide topology	<ol> <li>Auto illustrates the network topology including Zyxel non-Nebula devices.</li> <li>Help remote trouble shooting by showing device and link info. &amp; status.</li> <li>Automatic visual topology for Smart mesh.</li> <li>Device supports "Reboot" action.</li> <li>Switch PoE link supports "power cycle" action</li> </ol>		• •	VAR&IT	Site-wide > Topology	
•	✓ v	/ /	Summary report email & schedule	Send out site or device statistics, with logo options, by email now or by schedule.		•	MSP	Site-wide > Summary report Site-wide : Monitor > Access points / Switches / Firewall > Summary report	
•	√ v	<b>✓</b> ✓	365 days on	View up to 365 days statistics including sitewide, AP, SW, GW summary report (24 HR only on Base Pack).		7D •	VAR&IT	Site-wide > Summary report Site-wide > Monitor > Access points / Switches / Firewall > Summary report	>
•	√ v	/ /	365 days statistics on device monitoring	View device usage chart up to 365 days (24 HR only on Base Pack).		7D •	VAR&IT	Site-wide > Devices > Access points / Switches / Firewall > [Select AP / SW ]	
•	√ v	/ /	365 days statistics on client monitoring	View client traffic chart up to 365 days (24 HR only on Base Pack).		7D •	VAR&IT	Site-wide > Clients > [Select client]	

M M	2 R	F	S	W	Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
•	)	<b>√</b>	✓	✓	365 days statistics on device event log access	View event log chart up to 365 days (24HR only on Base Pack).		7D	•		Site-wide > Monitor > Access points / Switches / Firewall > Event log	
•		✓	✓	✓	Export data to CSV/XML file	Download the data currently displayed in the table of eg. Inventory, Cloud authentication etc. in either a CSV or XML file format.			•	VAR&IT	All monitoring pages with table data	
•		<b>√</b>	✓	✓	Open API	Open API for Ecosystem Partner Application Integration			•	MSP	Monitoring and a bit basic configuration related (keep updating, please check with PLM/AE for more details)	
•	)	✓	$\checkmark$	✓	DPPSK API access	Support to generate an API token (DPPSK third-party integration for now).			•	MSP	Site-wide > Configure > Site settings	
•	✓	<b>√</b>	<b>√</b>	✓	Smart email alerts	NCC integrates & intelligently scans at configuration changes, network topology, device status and security service events to send smart email alerts when necessary.		•	•	VAR&IT	Site-wide > Configure > Alert settings	
• •					Firmware upgrade schedules on a per- device basis	On top of scheduling site-wide firmware upgrade, you're also able to assign specific firmware upgrade time on particular (can be filtered and selected by tag, model, current version etc.) device.		•	•		Site-wide > Configure > Firmware Management	
•	<b>√</b>	<b>√</b>	<b>✓</b>	✓	Org-wide firmware upgrade	User can upgrade device's firmware across multiple sites. The Firmware Upgrades allows organization admins to manage firmware versions on a per-site and per-device type basis.		•	•		Organization-wide > Organization- wide manage > Firmware management	
•	✓	✓	✓	✓	Priority support reques (direct NCC)	tSend us support ticket directly from NCC UI and Nebula mobile APP and get case updates.	•		•	VAR&IT	Help > Support request	
•	<b>√</b>	✓	✓	✓	Web chat support (direct NCC)	Web chat with tech support directly from NCC UI.			•	VAR&IT	All website	
•	<b>√</b>	<b>√</b>	✓	<b>√</b>	Upload photo from Gallery	Upload up to 5 photos to NCC from phone's photo Gallery (1 photo only on Base and Plus Pack).	•		•	VADOIT	Site-wide > Devices (eg.Access points) > Access points > [Select AP] Photo	

3

W	<b>12</b>	R	F S	5	w	Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
(	•	✓ ,	√ v	/	✓	Remote CLI access / Configurator	Provide remote CLI access live tools to AP, Switch and Security Appliance and remote Web GUI access live tools to Mobile Router			•	VAR&IT	Site-wide > Devices > Access point / Switches / Firewall > [Select AP / SW / FW ] Live tools	
					✓		Provide administrators with a health condition overview of their wireless networks, per AP and per client, and quickly take actions to improve poor performance or user experience.			•	VAR&IT	Site-wide > Monitor > Access points > Wireless health	
					✓	Per AP (room) per SSID	Allow to set up programmable SSID & PSK for each AP				VAR&IT	Site-wide > Configure > Access points > SSID settings	
						Dynamic Personal Pre-Shared Key (DPPSK)	Allow the authentication of users with individual unique key to the wireless network. And also allow to use DPPSK as 2-Factor Auth. for IOT devices by email.			•		Site-wide > Configure > Access points > SSID advanced settings	
					✓	Voucher	Allow the authentication of users to the wireless network by sign-in with voucher code		•		VAR&IT	Site-wide > Monitor > Access points > Vouchers	
						Captive Portal MAC Auth. Fallback	To provide a better user experience, avoid captive portal with RADIUS re-authentication by falling back to MAC authentication when clients rejoin the network			•		Site-wide > Configure > Access points > SSID advanced settings	
					✓	RADIUS NAS ID customizable	Allow to set a NAS identifier to be used to identify location/Nebula site while integrating with an external captive portal service with RADIUS authentication.				MSP	Site-wide > Configure > Access points > SSID advanced settings	
						RADIUS accounting for captive portal	Enable to configure Radius accounting server settings for captive portal with RADIUS authentication.			•		Site-wide> Configure > Access points > SSID advanced settings	
					✓	Portal redirect URL parameter customization	Allow to customize the parameter sent to third party captive portal integration.			•	MSP	Site-wide> Configure > Access points > Captive portal customization	4

M M2 R	FS	W Feature	Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
		Smart steer ✓	ing per AP	Granularity control of the RSSI threshold settings per AP, for a more accurate deployment.			•	VAR&IT	Site-wide > Configure > Access points > Radio settings > [Edit the Selected AP]	
		BWM by VL interface	AN	Provide traffic shaping (rate-limit) to user/user group by assigning to different VLAN(s)			•	VAR&IT	points > Traffic shaping	Support model: NWA1123ACv3, WAC500, WAC500H, NWA110AX, NWA210AX, WAX510D, WAX610D, WAX630S, WAX650S
•		AP traffic Ic ✓	g	Allow to export the traffic log of the AP to a syslog server in NAT mode				VAR&IT	Site-wide > Configure > Site settings	
	✓	IPTV report		Provide utilization, network analysis including UPnP packet detection and client statistics of the multicast groups or channels in an IPTV environment, allowing to import channel list in advance.			•	MSP	Site-wide > Monitor > Switches > IPTV report	
	✓	Advanced	IGMP	Set IGMP snooping advanced settings such as role, mode, timers, unknown multi-cast drop per VLAN and IPTV topology setup for an effective bandwidth utilization design in an IPTV environment.				MSP	Site-wide > Configure > Switches > Advanced IGMP	
	<b>√</b>	Switch Surv Monitoring		Provide the advanced deployment and Fmaintenance page for the powered devices, ex. IP camera including ONVIF IPCAM discovery.			•	VAR&IT	Site-wide > Monitor > Switches > Surveillance	GS1350 series only for now
	✓	Auto PD Re	covery	Auto recover malfunctioning PD by taking advantage of their PoE dependency		•		VAR&IT	Site-wide > Configure > Switches > Switch ports > [Select Port]	Supporting GS1350 & GS2220 series
	✓	Vendor ID-I VLAN	oased	Allow to allocate network devices from different vendors into different VLANs for easy management and traffic priority.		•		VAR&IT	Site-wide > Configure > Switches > Switch settings	
	✓	IP Source G	Guard	Protect network access from illegal IP addressing configured by DHCP and/or manual/static setting				VAR&IT	Site-wide > Configure > Switches > Switch settings	
	<b>√</b>	IP interface	& static	Support Layer 3 function to create IP interface and IPv4 static route			•	VAR&IT	Site-wide > Configure > Switches > IP & Routing	

M M2 R	F S	W Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target Usei	r NCC Location	Note
	✓	Switch Stacking	Experience high-performance network management by managing multiple switches as a single entity, simplifying maintenance while increasing scalability.			•	VAR&IT	Site-wide > Configure > Switches > Stacking management	
•	✓		View Anti-virus/Application Patrol/Content Filtering/ Intrusion Detection and Prevention usage & hits of the network clients at the network level and per client level (24HR only on Base Pack).		7D	365D	MSP	Site-wide > Monitor > Security gateway > NSS analysis report	Requires NSG NSS-SP license to see the report
•	✓	Traffic log archiving	Collecting and archiving traffic log from Nebula security appliance. Customer can download archived traffic log from SecuReporter.			•	VAR&IT	Site-wide > Monitor > Firewall > SecuReporter	
	<b>√</b>	VPN topology with traffic usage	Provide visualize virtual private network connections & usage (per tunnel) between different sites of VPN networks (areas)			•	VAR&IT	Organization-wide > Organization-wide manage > VPN Orchestrator	
	✓	Smart VPN	Smart VPN configuration includes software- defined design to easily build scalable VPN networks (areas) and setup non-Nebula VPN peers among HQ and branches			•	VAR&IT	Organization-wide > Organization-wide manage > VPN Orchestrator	
	<b>√</b>	VPN provision script email	Send L2TP Client provisioning scrip by email for client VPN's quick setting			•	VAR&IT	Site-wide > Configure > Security gateway / Firewall > Remote access VPN (L2TP over IPSec VPN Server)	
	<b>√</b>	Collaborative Detection &  ✓ Response (CDR)* with automatically respond action	Support automatically block/quarantine clients based on the USG Flex UTM Security Pack's CDR policy.			•	VAR&IT	Site-wide > Configure > Collaborative detection & response	Requires USG Flex UTM Security Pack license to do CDR management
✓		Client device heartbeat (LAN device alive monitoring)	Effortlessly monitor mission-critical LAN devices, even in Mobile Operator private network environments.			•	VAR&IT	Site-wide > Devices > Mobile router	