KLEVV

CRAS XR RGB

DDR4 Gaming/OC Memory

Putting our brand spirit of "Creative Evolution" into practice, KLEVV proudly introduces our brand-new CRAS XR RGB DDR4 Gaming/OC Memory. The rule-breaking CRAS XR RGB adopts unique circular RGB light diffuser design, which makes RGB light flows even more vivid & eye-catching. With 16.8 million RGB color support, the astonishing light illumination of CRAS XR RGB is just like a feast for the eyes.

KLEVV CRAS XR RGB inherits the sophisticated product philosophy of signature CRAS series, and further establishes a new standard in design, quality & performance. For gamers, overclockers, and enthusiasts around the world, KLEVV is committed to bring you the most sensational & fabulous user experience!

XMP 2.0 One-step OC	**RGB Light** Support	**Performance** Upgraded	**QVL** Verified	**Support Intel/** AMD Platforms

Features

- Special circular light diffuser design to show dual RGB bars from top view
- 16.8 million RGB color support for astonishing light illumination
- Support RGB control software synchronization of ASUS/ MSI/ GIGABYTE/ ASROCK/ Razer
- Aluminum heat spreader for thermal conductivity
- Highest quality and reliability through rigorous test procedures
- Reduced voltage and ultra-lower power consumption
- QVL approved and compatible with mainstream motherboards/platforms

Ordering Information

Speed	Capacity	Product Number	EAN Code
3600	8GB(8x1)	KD48GU880-36A180Y	4895194966708
	16GB(8x2)	KD48GU880-36A180Z	4895194966722
	16GB(16x1)	KD4AGU880-36A180Y	4895194966715
	32GB(16x2)	KD4AGU880-36A180Z	4895194966739
4000	8GB(8x1)	KD48GU880-40B190Y	4895194966753
	16GB(8x2)	KD48GU880-40B190Z	4895194966746
4266	8GB(8x1)	KD48GU880-42B190Y	4895194966760
	16GB(8x2)	KD48GU880-42B190Z	4895194966777

RAZER CHROMA RGB | AURA SYNC | RGB FUSION 2.0 GIGABYTE | msi MYSTIC LIGHT SYNC | ASRock POLYCHROME SYNC | AMD RYZEN | intel XMP2.0

Specifications

Type	DDR4 Unbuffered DIMM		
Capacity	8GB(8x1)	16GB(8x2)	16GB(16x1), 32GB(16x2)
Speed/ CAS Latency/ Voltage 3600	18-22-22-42@1.35V	18-22-22-42@1.35V	18-22-22-42@1.35V
4000	19-25-25-45@1.4V	19-25-25-45@1.4V	-
4266	19-26-26-46@1.4V	19-26-26-46@1.4V	-
Dimensions	(L)137.4 x (W)42.5 x (H)8.3 mm		
Warranty	Limited Lifetime Warranty		