

Gigabit Ethernet PCI-E Adapter

AD1103



Features:

>Support PCI-E interface

>Complies with IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE802.3ab 1000Base-T standards

>Supports Full-Duplex, up to 20/200/2000M network bandwidth

>Supports RPL/PXE BOOT-ROM

>Supports Windows 2000/ Windows XP/ Windows Vista/ Windows 7/Windows 8/Windows 8.1, Linux, MAC OS

Brief:

The netis AD1103 is a 10/100/1000Mbps, PCI-E interface adapter, which reduces CPU loading using bus master architecture. It also supports WOL and RPL/PXE BOOT-ROM. With single UTP/STP and the Auto-Negotiation (Nway) function, the adapter can auto-negotiate 10Mbps, 100Mbps or 1000Mbps speed, and half or full duplex mode with its link partner (a hub, for example). Featured with a wide compatibility with the major operating systems, it provides a good choice for you to upgrade the network

Specification:

Hardware	
Standard	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE802.3ab 1000Base-T
Interface	32-bit PCI-E 1*10/100/1000Mbps RJ45 port, Auto-Negotiation, Auto MDI/MDIX
LED	LNT/ACT, 1000M
Data Transmission Rate	10/100/1000Mbps(Half-duplex) 20/200/2000Mbps(Full-duplex)
WOL	Supported
RPL/PXE BOOT-ROM	Supported
Network Driver	Windows 2000, Windows XP (32/64bits), Windows Vista (32/64bits), Windows 7 (32/64bits), Windows 8 (32/64bits), Windows 8.1 (32/64bits); Linux; MAC OS 10.4/10.5/10.6/10.7
Others	
Certification	FCC, CE
Environment	Operating Temperature: 0℃~40℃ Storage Temperature: -40℃~70℃ Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Package	1 * AD1103 1 * Quick Installation Guide 1 * Driver CD

Topological Graph:

