



Make It Yours.

ELITE 500 230V - V3

MPW-5001-ACABN1

POWER UP



FEATURES

Active PFC + Forward Topology Design : Constructed with protective measures normally found in high-end power supplies to increase safety and current stability.

High Temperature Resistance : Capable of operating at 40°C under full load allowing a longer lifespan in warmer environments.

Peak Power Tolerance : Can reliably push an additional 50W at peak power load for up to 10 seconds.

75% Efficiency : Maintains an average efficiency of 75% at 50% load.

Durable, Reliable, and Safe : Will perform consistently in whatever environment whether it's high altitudes or ultra humid settings.

3 Year Warranty : This unit comes with a standard limited manufacturing warranty of 3 years from the date of purchase.

PACKAGE INFORMATION

Cable Type	EAN	UPC
AU	4719512066225	884102038747
BR	4719512066232	884102038754
EU	4719512066201	884102038723
HK	4719512066287	884102038808
IN	4719512066188	884102038709
KR	4719512066249	884102038761
PH	4719512066195	884102038716
ST	4719512066218	884102038730
UK	4719512066171	884102038693

Nett Weight	0.002 kg / 0.004 lb
Gross Weight	0.002 kg / 0.004 lb
Package Dimensions	213 x 195 x 96mm (8.39 x 7.68 x 3.78")
Carton Dimensions	500 x 228 x 215mm (19.69 x 8.98 x 8.46")
Unit / Carton	5 pcs
Carton / Pallet	50 pcs

The Elite - v3 power supply unit is a dependable choice for entry level users and system integrators. The quiet 120mm fan, Active PFC, and 3 year warranty deliver a PSU that provides function and resilience you can count on. It's the perfect option for work horse systems stored and operated in less than ideal conditions and climates. This power supply unit has been engineered for reliability with a focus on reducing random shutdowns in conditions where power sources are inconsistent and unstable. The Elite - v3 is a complete solution, offering performance and stability at an affordable price.

SPECIFICATIONS

Product Name	Elite 500 230V - v3		
Item Code	MPW-5001-ACABN1		
ATX Version	ATX 12V Ver. 2.41		
PFC	Active PFC		
Input Voltage	200 - 240V		
Input Current	5A		
Input Frequency	50 - 60Hz		
Dimensions (L x W x H)	140 x 150 x 86mm		
Fan Size	120mm		
Fan Bearing	Sleeve Bearing		
Efficiency	75% @ Typical Load		
80 PLUS Rating	Non 80 PLUS		
ErP 2014 Lot 3	Yes		
Power Good Signal	100 - 500 ms		
Hold Up Time	>14ms at 100% load		
MTBF	>100,000 hours		
Protections	OVP / OPP / OTP / SCP / UVP		
Regulatory	TUV / CE / CB		
Connectors	ATX 24 Pin	x1	
	EPS 4+4 Pin	x1	
	SATA	x5	
	Peripheral 4 Pin	x3	
	PCI-e 6+2 Pin	x2	

AC INPUT	200 - 240V~ 5A 50 - 60Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vstb
	14A	16A	38A	0.3A	2.5A
TOTAL POWER	110W		456W	3.6W	12.5W
	500W				