



Make It Yours.

V750 GOLD - v2 (WHITE EDITION)

MPY-750V-AGBAG

POWER UP



FEATURES

80 PLUS Gold Certified : This certification guarantees a typical efficiency of 90% under normal operating conditions.

Performance Driven Topology : The half-bridge LLC resonant converter and DC-DC technology offer reliable and stable voltage outputs for safer, more reliable performance and higher efficiency.

Semi-Fanless Mode with Hybrid Switch : The 135mm FDB fan is semi-fanless up to 40% load and can be manually turned off with a hardware based hybrid switch.

Full-Modular Cabling : Modular cables reduce clutter, increase airflow, and improve overall efficiency and thermal performance.

16 AWG PCI-e Cables : The thicker 16 AWG PCI-e cables allow for higher currents, thereby improving both efficiency and safety.

10 Year Warranty : This unit comes with a standard limited manufacturing warranty of 10 years from the date of purchase.

PACKAGE INFORMATION

Cable Type	EAN	UPC
AU	4719512068588	884102041099
BR	4719512068595	884102041105
EU	4719512068564	884102041075
JP	4719512068625	884102041136
KR	4719512068601	884102041112
ST	4719512068571	884102041082
TW	4719512068694	884102041204
UK	4719512068557	884102041068
US	4719512068540	884102041051

Nett Weight	2.12 kg / 4.674 lb
Gross Weight	2.65 kg / 5.842 lb
Package Dimensions	303 x 202 x 125mm (11.93 x 7.95 x 4.92")
Carton Dimensions	520 x 318 x 238mm (20.47 x 12.52 x 9.37")
Unit / Carton	4 pcs
Carton / Pallet	24 pcs

The V Gold - v2 offers the high quality user experience you've always wanted. Enjoy an 80 Plus Gold efficiency rating, full-modular cabling, semi-fanless operation, a 135mm FDB fan, 16AWG PCIe high efficiency cables, and a 10 year warranty. Improvements and innovations from the components to the cables deliver a power supply unit fit for any and every type of PC. The 100% Japanese capacitors, half-bridge LLC resonant convertor, and DC-DC circuitry deliver a product that even the pros can respect, at 550, 650, 750, and 850 watt levels. Also available with black casing and cables.

SPECIFICATIONS

Product Name	V750 Gold - v2 (White Edition)				
Item Code	MPY-750V-AGBAG				
ATX Version	ATX 12V Ver. 2.52				
PFC	Active PFC				
Input Voltage	100-240V				
Input Current	10-5A				
Input Frequency	50-60Hz				
Dimensions (L x W x H)	160 x 150 x 86mm				
Fan Size	135mm				
Fan Bearing	FDB				
Fan Speed	1545 RPM				
Noise @ 20%	0 dBA				
Noise @ 50%	23.6 dBA				
Noise @ 100%	32.5 dBA				
Efficiency	90% @ Typical Load				
80 PLUS Rating	80 PLUS Gold				
ErP 2014 Lot 3	Yes				
Operating Temperature	0-50°C				
Power Good Signal	100-500ms				
Hold Up Time	17ms				
MTBF	>100,000 hours				
Protections	OVP / OPP / SCP / OCP / UVP / OTP				
Regulatory	CCC, CE, TUV-RH, RCM, EAC, cTUVus, FCC, BSMI, KC, CB				
Connectors	ATX 24 Pin	x1			
	EPS 4+4 Pin	x1			
	EPS 8 Pin	x1			
	SATA	x12			
	Peripheral 4 Pin	x4			
	FDD	x0			
	PCI-e 6+2 Pin	x4			

AC INPUT	100-240V~ 10-5A 50-60Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vstb
	20A	20A	62A	0.3A	3A
TOTAL POWER	130W		744W	3.6W	15W
	750W				

FEATURES




This certification guarantees a typical efficiency of 90% under normal operating conditions.



The half-bridge LLC resonant converter and DC-DC technology offer reliable and stable voltage outputs for safer, more reliable performance and higher efficiency.



The 135mm FDB fan is semi-fanless up to 40% load and can be manually turned off with a hardware based hybrid switch.



Modular cables reduce clutter, increase airflow, and improve overall efficiency and thermal performance.



The thicker 16 AWG PCI-e cables allow for higher currents, thereby improving both efficiency and safety.



This unit comes with a standard limited manufacturing warranty of 10 years from the date of purchase.