

PATH TO THE FUTURE

Découvrez l'écran gaming MSI MAG 255XF ! Cet écran de 24,5" à dalle Rapid IPS et résolution Full HD offre un taux de rafraîchissement de 300 Hz et un temps de réponse de 0,5 ms (gris à gris, minimum) qui vous permettent de prendre l'avantage sur vos adversaires dans toutes vos parties !



Picture and logos

SELLING POINTS

- Dalle Rapid IPS pour des couleurs et une luminosité optimales
- Taux de rafraîchissement de 300 Hz pour un affichage sans ralentissement
- Temps de réponse gris à gris de 0,5 ms minimum pour des images sans déchirures ni saccades
- Nouvelle technologie AI Vision cadencée par l'IA pour mieux discerner les détails dans les zones sombres
- Réduction de la lumière bleue pour une utilisation confortable



1. 5-way Joystick Navigator
2. AC-in
3. 2x HDMI™ 2.0b(FHD@240Hz)
4. Display Port 1.2a
5. Earphone out
6. Kensington Lock

SPECIFICATION

Modèle	Part No	9S6-3BC21M-061
	Color	ID1/Black-Black
Affichage	Screen Size	24.5" (62.23cm)
	Active Display Area (mm)	543.744(H) x 302.616(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~300Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	53.28~333 KHz(H) / 48~300 Hz(V)
	Refresh Rate	300Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	105%/81%
	NTSC (CIE1931 area percentage/overlap)	79%/71%
	sRGB (CIE1976 area percentage/overlap)	120%/97%
	sRGB (CIE1931 area percentage/overlap)	113%/98%
	Adobe RGB (CIE1976 area percentage/overlap)	103%/87%
	Adobe RGB (CIE1931 area percentage/overlap)	75%/76%
	DCI-P3 (CIE1976 area percentage/overlap)	90%/90%
	DCI-P3 (CIE1931 area percentage/overlap)	83%/81%
	Rec.709 (CIE1976 area percentage/overlap)	120%/97%
	Rec.709 (CIE1931 area percentage/overlap)	113%/98%
	Rec.2020 (CIE1976 area percentage/overlap)	69%/69%
	Rec.2020 (CIE1931 area percentage/overlap)	59%/59%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
Ports E/S	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

Accessoires	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	557.1 x 220.1 x 418.5
	Product Dimension without Stand (WxDxH) (mm)	557.1 x 66.4 x 326.9
	Stand Dimension (WxDxH) (mm)	318.0 x 220.1 x 142.5
	Weight (Net kg)	3.24
	Weight Without Stand (kg)	2.82
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	63 x 12.5 x 41.1
	Outer Carton Dimension (WxDxH) (cm)	65 x 14.5 x 44.3
	Weight (Gross kg)	5.13
Code-barre	EAN	4711377330374