

## PATH TO THE FUTURE

Découvrez l'écran gaming MSI MAG 32CQ6F, un modèle 32 pouces de dernière génération qui offre une résolution WQHD, un taux de rafraîchissement de 180 Hz et un temps de réponse GtG minimum de seulement 0,5 ms. Avec le MSI MAG 32CQ6F, préparez-vous à prendre l'avantage sur vos opposants dans toutes vos batailles.



Picture and logos

## SELLING POINTS

- Dalle Rapid VA avec temps de réponse GtG minimum de 0,5 ms pour des couleurs et une luminosité optimales
- Taux de rafraîchissement de 180 Hz pour un affichage sans ralentissement
- Temps de réponse GtG minimum de 0,5 ms pour des images sans déchirures ni saccades
- AI Vision pour mieux discerner les détails dans les zones sombres mais également améliorer la luminosité et la saturation des couleurs
- AMD FreeSync™ pour des images extrêmement fluides
- Réduction de la lumière bleue pour une utilisation confortable



1. 1 x bouton de navigation à 5 directions
2. 1 x entrée alimentation
3. 2 x HDMI™ 2.0b(WQHD@144Hz)
4. 1 x Display Port 1.4
5. 1 x sortie audio
6. 1 x encoche Kensington

## SPECIFICATION

Modèle	Part No	9S6-3DC91M-026
	Color	ID1/Black-Black
Affichage	Screen Size	31.5" (80.01 cm)
	Active Display Area (mm)	697.344 (H) x 392.256 (V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2724(H)x0.2724(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	DisplayHDR 400
	SDR Brightness (nits)	400
	HDR Brightness (Peak nits)	400
	Contrast Ratio	3500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	70.08~266.4 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	85%/80%
	NTSC (CIE1931 area percentage/overlap)	72%/72%
	sRGB (CIE1976 area percentage/overlap)	101%/95%
	sRGB (CIE1931 area percentage/overlap)	105%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	85%/82%
	Adobe RGB (CIE1931 area percentage/overlap)	78%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	78%/78%
	DCI-P3 (CIE1931 area percentage/overlap)	78%/75%
	Rec.709 (CIE1976 area percentage/overlap)	101%/95%
	Rec.709 (CIE1931 area percentage/overlap)	105%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	56%/56%
	Rec.2020 (CIE1931 area percentage/overlap)	54%/54%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
Ports E/S	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	32
	Annual Energy Consumption (KWh)	47
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C13	

Accessoires	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	709.4 x 507.2 x 249.8
	Product Dimension without Stand (WxDxH) (mm)	709.4 x 419.1 x 107.2
	Stand Dimension (WxDxH) (mm)	339.8 x 249.8 x 143
	Weight (Net kg)	5.3
	Weight Without Stand (kg)	4.8
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	80 x 17 x 51.4
	Outer Carton Dimension (WxDxH) (cm)	81.8 x 18.8 x 54.9
	Weight (Gross kg)	8.4
Code-barre	EAN	4711377332224