



- 120mm Fan
- Active PFC Design
- Single Rail
- Industrial level protection with OVP, SCP, OPP, UVP

SPECIFICATIONS

WEIGHT (CARD)	169g
Dimensions	120mm x 120mm x 25.6mm
Modular	Non-Modular
Fan Bearing	Hydraulic Bearing
Bearing Type	Hydro-Dynamic Bearing
Rated Speed	500 - 1800 ±15% RPM
Power Watt	500W
Air Flow	19.79 - 71.27 CFM
Input Voltage	200-240~
Input Frequency Range	50~60Hz
Static Air Pressure	0.16 - 2.09 mm-H2O
Connector	4-Pin PWM/DC
ATX (24 pin)	1
Life Expectancy	MTTF 150,000 Hours (25°C)
EPS (4+4 pin)	2
Fan Size	120 mm
Dimension	140mm x 150mm x 86mm / 5.51 x 5.9 x 3.38 inches
PCI-E (6+2 pin)	1
PFC Type	Active PFC
SATA (15 pin)	3
Protection	OCP, OPP, SCP, UVP
MOLEX (4 pin)	2
FDD (4 pin)	1

MAG A500N-H					
AC INPUT		200-240V, 6.3A , 50-60Hz			
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vsb
	14A	14A	38A	0.3A	2.5A



POWER - SUPPLY

MAG A500N-H

YOUR POWER, RIGHT AWAY

MAG A500N-H				
TOTAL POWER	105W	456W	3.6W	12.5W
	500W			

CONNECTOR					
ATX	EPS	PCI-E	SATA	PERIPHERAL	FDD
1	2	1	3	5	1