

# FS7 FS7R

Case Fan



## Features:

- Support ARGB sync
- PWM intelligent fan speed control
- Hydraulic bearing fan for durability and silent operation



CASE FAN  
FS7 / FS7R

VER250225BN

# SPECIFICATIONS

PART NUMBER	FS7-BK / FS7-BK-1IN1 FS7-WH / FS7-WH-1IN1
CONNECTOR	3-pin (ARGB) + 4-pin (PWM)
MODEL	DF1202512SEMN
AIRFLOW DIRECTION	Standard
DIMENSION (L x W x H)	120 x 120 x 25 mm
FAN RATED VOLTAGE	DC 12V
FAN RATED CURRENT	0.2 A $\pm$ 10%
FAN RATED POWER	2.4 W $\pm$ 10%
FAN LEAVES	7
CABLE LENGTH	500 mm $\pm$ 10%
BEARING	Hydraulic bearing
MAX AIRFLOW	37.02 CFM
STATIC PRESSURE	1.33 mm-H <sub>2</sub> O
SPEED	600 - 1800 $\pm$ 10% RPM
NOISE LEVEL	$\leq$ 41.5 dB(A) @ 300 mm
LED TYPE	ARGB
LED VOLTAGE	5V
LED CURRENT	0.58 A $\pm$ 10%
LED MAX. POWER	2.9 W $\pm$ 10%

# SPECIFICATIONS

PART NUMBER	FS7R-BK / FS7R-BK-1IN1 FS7R-WH / FS7R-WH-1IN1
CONNECTOR	3-pin (ARGB) + 4-pin (PWM)
MODEL	DF1202512SEMN
AIRFLOW DIRECTION	Reverse
DIMENSION (L x W x H)	120 x 120 x 25 mm
FAN RATED VOLTAGE	DC 12V
FAN RATED CURRENT	0.2 A $\pm$ 10%
FAN RATED POWER	2.4 W $\pm$ 10%
FAN LEAVES	7
CABLE LENGTH	500 mm $\pm$ 10%
BEARING	Hydraulic bearing
MAX AIRFLOW	27.09 CFM
STATIC PRESSURE	1.07 mm-H <sub>2</sub> O
SPEED	600 - 1800 $\pm$ 10% RPM
NOISE LEVEL	$\leq$ 37.8 dB(A) @ 300 mm
LED TYPE	ARGB
LED VOLTAGE	5V
LED CURRENT	0.58 A $\pm$ 10%
LED MAX. POWER	2.9 W $\pm$ 10%

# PICTURES

