



Platimax II

1200DF ATX 3.1 POWER SUPPLY



EPS1200P-NPX-W

Platimax II

1200DF ATX 3.1 POWER SUPPLY

Black / White




EPS1200P-NPX

- Integrated with Intel ATX 3.1 & PCIe 5.1 Standards
- Fully Modular Design with 80 PLUS® and CYBENETICS Platinum Certification
- Native 12V-2x6 Cable Supporting Up to 600W GPU Power
- Industrial-Grade 100% Japanese Capacitors
- 135mm D.F. Fan with Smart Control
- Mesh-sleeved Cables with Cable Comb Kit Included




Features

- **ATX 3.1 & PCIe 5.1 Ready**
 - Fully compliant with Intel ATX 3.1 and PCIe 5.1 standards, featuring a native 600W 12V-2x6 connector for next-gen GPUs.
- **Efficiency**
 - Achieves up to 92% efficiency at 50% load, and $\geq 70\%$ efficiency at 2% low load.
- **Extreme Power Excursion Support**
 - Handles up to 235% power excursion (0.1ms), ideal for high-performance GPU spikes.
- **Silent and Durable Cooling**
 - Equipped with a 135mm D.F. fan and 100% Japanese capacitors for over 100,000 hours MTBF at 25°C full load.
- **Fully Modular with Comprehensive Protections**
 - Fully modular cable design with built-in protections: OVP, OPP, OCP, SCP, OTP, UVP; certified for operation up to 5000m altitude.



Ready for Intel ATX 3.1




Native 12V-2x6 Cable Channels up to 600W Power to PCIe 5.1 Graphics Cards








Dust-Free Rotation (DFR) Function with Switch Button

Dimension

Unit : mm



Cables & Connectors

Model	Connectors					
						
1200W	1	2	1	3	8	4

Specifications

General Data

80 PLUS Efficiency	Platinum
Modular	Fully Modular
Cable Type	Individually Mesh-Sleeved Cable
Fan Size (mm)	135
Operating Temperature (°C)	50
MTBF (hrs)	>100K
Protections	OVP, OPP, OCP, SCP, OTP, UVP

Power Output

Model	EPS1200P-NPX	EPS1200P-NPX-W
AC Input Voltage	100-240VAC, 50-60Hz 200-240VAC, 50-60Hz(for China only)	
AC Input Current	15-8A 8A(for China only)	
DC Output		
	Rated	Combined
+3.3V	20A	100W
+5V	20A	
+12V	100A	1200W
-12V	0.4A	4.8W
+5Vsb	3.0A	15W
Total Power	1200W	
Dimensions	150(W)*86(H)*150(D) mm	



Logistics Information

Model	EPS1200P-NPX	EPS1200P-NPX-W
Barcode	EAN	4713157728579
	UPC	819315028575
Package Dimensions	330 x 195 x 130mm	
Gross Weight / Unit	3.19 kg	
Carton Dimensions	605 x 345 x 290 mm	
Q' ty / Carton	6 pcs	
Gross Weight / Carton	20.73 kg	